

Painter and Decorator

8. when painting galvanized metal, what would you use to prevent peeling?
- A a sealant with silicone B a top coat with latex paint
 C a primer with phosphoric acid D a finish with oil-based varnish
9. what is the purpose of drying agent
- A to prevent dehydration B to defend against bacteria
 C to absorb oxygen D to regulate temperature
10. a compressor used to operate a multiple line sprayer should be run at
- A 50-60 psi B 70-80 psi
 C 90-100 psi D 30-40 psi
11. when spraying , the gun should be _____.
- A far away from the wall B at an angle to the wall
 C directly against the wall D a consistent distance from the wall
12. Why was dry fall/fog coatings created?
- A To prevent damage caused by overspray B To enhance the color of the paint
 C To speed up the drying time of the paint D To create a textured finish on the surface
13. When new drywall nails are installed in sheetrock, they should be covered with _____.
- A joint compound B caulk
 C spackle D paint primer
14. Protruding framing members should be _____
- A left as is B covered with drywall
 C painted over D trimmed or reinstalled

Painter and Decorator

1074. Measure of self-leveling; characteristics of a coating allowing it to level or spread into a smooth film of uniform thickness before hardening.

- A Butadiene B Volume
 C Pressure D Flow

1075. Steel bars used to strengthen concrete

- A Structural steel B Sheet steel
 C Reinforcing steel D Carbon steel

1076. For use in fire-rated assemblies.

- A Coreboard B Cement board
 C Wallboard D Type x gypsum board

1077. Specially processed to give certain specific surface characteristics and used for exposed masonry surfaces.

- A Sand-struck brick B Facing brick
 C Glazed brick D Neither

1078. Brick bond pattern that every sixth course is composed of flemish headers.

- A Running bond B Bond stones
 C Flemish bond D Common bond

1079. Wood sheathing whose edges are rabbeted to make an overlapping joint.

- A Board siding B Shiplap siding
 C Bevel siding D Neither

1080. Used as a permanent form in the casting of gypsum concrete roof decks.

- A Masonry cement B Lime mortar
 C Fire brick D Gypsum formboard

Painter and Decorator

1081. The major cause of paint blisters on wood siding and exterior surfaces is caused by?

- A applying paint to a surface containing excessive moisture
- B applying paint in direct sunlight
- C painting during cold weather conditions
- D using a paintbrush that is too large for the surface

1082. what is the advantage of nylon bristles over natural when used on latex paint?

- A Nylon bristles are more expensive than natural
- B Nylon bristles are less effective on wood surfaces
- C Natural bristles are easier to clean than nylon
- D Natural bristles soften up with latex

1083. A blond finish is accomplished by

- A using a dark paint to cover the surface
- B applying a light stain over bleaching
- C sanding the wood to a fine finish
- D applying a clear coat without any stain