



1. A tri-axle trailer is equipped with five S-cam slack adjusters correctly set at an effective length of 6 inches and one incorrectly installed at 5 1/2 inches. How much less brake torque will be applied at the brake with the incorrectly set slack adjuster when the service application pressure is 100 psi on a 30-square-inch chamber?

<input type="radio"/> A 1,500 lb-in	<input type="radio"/> B 1,750 lb-in
<input type="radio"/> C 1,700 lb-in	<input type="radio"/> D 1,250 lb-in
2. A spring pack has a single cracked leaf. Technician A says that the spring pack should be replaced as a unit. Technician B says that the fractured leaf can be repair welded providing it is not the main leaf. Who is correct?

<input type="radio"/> A B only	<input type="radio"/> B A only
<input type="radio"/> C Both	<input type="radio"/> D Neither
3. Technician A says that it is good practice to machine a new drum before putting it into service because it trues the drum to the wheel. Technician B says that most heat discoloration and checking is easy to remove on used drums when brakes are serviced by skimming the drum on a lathe. Who is correct?

<input type="radio"/> A B only	<input type="radio"/> B A only
<input type="radio"/> C Both	<input type="radio"/> D Neither
4. Before testing a dual-drive axle truck equipped with ATC on a chassis dynamometer, what should be done?

<input type="radio"/> A ATC should be calibrated.	<input type="radio"/> B ATC must be disabled.
<input type="radio"/> C ATC settings should be adjusted.	<input type="radio"/> D ATC must be activated.
5. Technician A says that he seats radial tire beads by igniting a charge of ether inside the tire. Technician B says that he seats radial tire beads using a metal ring inflation aid. Who is correct?

<input type="radio"/> A B only	<input type="radio"/> B A only
<input type="radio"/> C Both	<input type="radio"/> D Neither

Transport Trailer Technician

11. What is the required amount of slack adjuster free travel on a properly adjusted, manual S-cam brake?
- A 1/4 to 1/2 inch B 1/2 to 3/4 inch
 C 3/8 to 5/8 inch D 5/8 to 7/8 inch
12. Technician A says that a damaged floor in a unibody van trailer should be immediately repaired because the floor forms part of the frame. Technician B says that an out-of-square door frame on a unibody van trailer can indicate problems with the structural integrity of the vehicle. Who is correct?
- A B only B A only
 C Both D Neither
13. When performing a front-end alignment, Technician A checks and corrects the toe setting first. Technician B says that to measure toe using a tape and tram gauge, it is necessary to make measurements between the tires at both the front and back at hub height. Who is correct?
- A B only B A only
 C Both D Neither
14. A leaking axle seal has saturated the brake shoe linings and caused them to glaze. Technician A says that the shoes should be immersed in solvent before being returned to service. Technician B says that if the brake shoes on both sides of the axle are not replaced, brake torque balance could be affected. Who is correct?
- A B only B A only
 C Both D Neither
15. When C-channel stock is used for a frame reinforcement, which of the following must be true?
- A It must be lighter than the original frame rail. B It must have the same yield strength as the original frame rail.
 C It must be made of a different material than the original frame rail. D It must be more flexible than the original frame rail.

Transport Trailer Technician

16. When an S-cam foundation brake slack adjuster is in the fully applied position, ideally the slack adjuster-to-pushrod angle should be:
- A slightly less than 90 degrees B exactly 45 degrees
 C exactly 90 degrees D slightly more than 90 degrees
17. Technician A says that an advantage of disc wheels over cast spoke is that they produce fewer wheel alignment problems. Technician B says that in stud-piloted disc wheel systems, a loose inner nut can easily go undetected, eventually pounding out the ball seat. Who is correct?
- A B only B A only
 C Both D Neither
18. When adjusting a manual slack adjuster on an S-cam foundation brake, Technician A says that the lock collar should be retracted and the adjusting nut always rotated clockwise to decrease free travel. Technician B says that free travel can be reduced only when the adjusting nut is rotated counterclockwise. Who is correct?
- A B only B A only
 C Both D Neither
19. A set of brake linings has become glazed because of oil saturation by a failed wheel seal. Technician A says that pressure washing the foundation brake components should be sufficient to remove the effects of the oil saturation. Technician B says that the best practice is to replace the brake linings on both wheels on the affected axle. Who is correct?
- A B only B A only
 C Both D Neither
20. Technician A says that when fifth wheel brackets are bolted to frame rails, the section modulus over that section of the frame is increased. Technician B says that installing inverted L-section reinforcements is preferred to L-section reinforcements because the section modulus is not affected. Who is correct?
- A B only B A only
 C Both D Neither